

## Latest Cisco 642-732 Exam Questions - Download From Braindump2go Promise Pass 100% OR Money Back!

CISCO OFFICIAL EXAM CENTER: 642-732 Exam Questions has been Updated Today! Real Latest 642-732 Exam Questions Updated By Official Cisco Exam Center! Braindump2go Offers 642-732 Dumps sample questions for free download now! You also can visit our website, download our premium Cisco 642-732 Exam Real Answers, 100% Exam Pass Guaranteed!**Keywords:** **642-732 Exam Dumps,642-732 Practice Tests,642-732 Practice Exams,642-732 Exam Questions,642-732 PDF,642-732 VCE Free,642-732 Book,642-732 E-Book,642-732 Study Guide,642-732 Braindump,642-732 Prep Guide**

Compared Before Buying Cisco

Pass4sure	Braindump2go
Not In Stock	100% Pass OR Money Back
/	167 Q&As - Real Exams
/	\$99.99
/	Coupon Code: B

QUESTION 121 Which choice best describes RF challenges for outdoor mesh site survey and deployment? A. Reflection B. Reflection, absorption C. Diffraction D. Diffraction, scattering E. Reflection, absorption, diffraction, scattering Answer: E  
QUESTION 122 Refer to the exhibit. After performing a Layer 1 survey using Cisco Spectrum Expert, which result is indicated by the visual screen?



A. Normal 802.11b activity B. Normal 802.11g activity C. Microwave oven interference D. Video camera interference E. Bluetooth device interference Answer: A  
QUESTION 123 What document is required to build the Statement of Work? A. pre-survey questionnaire B. post-survey questionnaire C. site survey report D. installation report Answer: A  
QUESTION 124 What RF phenomenon results from a presence of metallic I-beams, conveyor belts, chain-link fences, and metallic shelves found in a warehousing environment? A. multipath B. free path loss C. absorption D. scattering Answer: A  
QUESTION 125 Which two are impacts of having 802.11b clients in an 802.11g network? (Choose two.) A. 802.11b clients will degrade throughput of 802.11g clients B. 802.11b is more susceptible to multipath than 802.11g C. 802.11b operates over fewer channels than 802.11g D. 802.11b uses 20 MHz wide channels, 802.11g uses 40 MHz wide channels E. 802.11b is more susceptible to attenuation than 802.11g Answer: AB  
QUESTION 126 What type of survey is used to assess and analyze existing wireless infrastructure? A. passive survey B. active survey C. predictive survey D. application survey Answer: A  
QUESTION 127 When planning a site survey, what Cisco tool can an engineer use to estimate the number of required APs? A. MSE Location Tracking B. WCS Planning Mode C. WLC NetFlow Exporter D. LWAP Monitor Mode E. WCS Map Editor Answer: B  
QUESTION 128 The wireless survey report shows APs staggered throughout a facility, with several of them placed right on the exterior walls. Other APs are located right at building corners and major turns in the structure layout. Assuming all survey locations are optimized with a minimum of -67 RSSI at cell edges with 20% overlapping cells, for what purpose can this survey model be used? A. location based services and BYOD preparation B. voice and data clients with video on demand C. streaming video with VoIP and data as an option D. location services, VoIP, data, and video Answer: D  
QUESTION 129 A customer wants to deploy wireless services inside a 500-seat auditorium. Given the volume of potential users in this condensed area, what is the best option for AP deployment?

A. place 802.11n APs along the outside edge with dual-band directional antennas  
B. place 802.11n APs along the outside edge with 2.4GHz directional antennas  
C. place 802.11n APs along the outside edge with 5GHz directional antennas  
D. place 802.11n APs in the center with 2.4GHz sector antennas  
E. place 802.11n APs in the center with 5GHz sector antennas  
F. place 802.11n APs in the center with dual-band sector antennas  
Answer: B  
QUESTION 130  
A wireless engineer is gathering equipment to perform a point-to-point bridge survey. What three pieces of equipment should be used? (Choose three.)  
A. 3502i with dual band directional antennas  
B. 3502e with AIR-ANT2460NP-RC.  
C. 1132 with a 10dBi Yagi  
D. 1552e with three AIR-ANT2547-N=E.  
E. 1552e with AIR-ANT2588P3M-N=F.  
F. 1310 with internal antenna  
G. 1142 Series with internal antennas  
Answer: BEF  
QUESTION 131  
What three best practices should be performed for a Data-Only Survey? (Choose three.)  
A. reduce the power to 50% of the client max power  
B. reduce the power to 75% of the client max power  
C. disable DTPCD.  
D. enable DTPCE.  
E. 5 - 10 percent overlap  
F. 10 - 15 percent overlap  
Answer: ACF  
QUESTION 132  
What are the best practice minimum and recommended signal level values for a Location Services Survey?  
A. minimum: -65dBm; recommended: 60 dBm  
B. minimum: -70dBm; recommended: -68 dBm  
C. minimum: -75dBm; recommended: -72dBm  
D. minimum: -80dBm; recommended: -78dBm  
Answer: C  
2015 Latest Released Cisco 642-732 Exam Dumps Free Download From Braindump2go Now! All Questions and Answers are checked again by Braindump2go Experts Team, 100% Real Questions and Correct Answers Guaranteed! Full Money Back Guarantee Show our Confidence in helping you have a 100% Success of Exam 642-732! Just have a try!

**Compared Before Buying Cisco 642-732**

Pass4sure	Braindump2go
Not In Stock	100% Pass OR Money Back
/	167 Q&As - Real Questions
/	\$99.99
/	Coupon Code: BDNT2014

<http://www.braindump2go.com/642-732.html>